


Communication & Low Voltage

Communication & Low Voltage



- Supports cable from #12 wire thru $\frac{3}{8}$ " threaded rod.
- Qwik-Latch cable retainer included with each hook.
- W2 series attaches to #12 wire thru $\frac{1}{4}$ " plain or threaded rod.
- W6 series attaches to $\frac{3}{8}$ " plain or threaded rod.
- Static Load Capacity: 25 Lbs.
- Finish: Pre-galvanized

Cable To Wire and Rod Fasteners



UPC/Part Number	Catalog Number	Description	Box Qty.
782051 28081	BCH12-W2	$\frac{3}{4}$ "	50
781011 04819	BCH21-W2	$1\frac{5}{16}$ "	50
781011 04841	BCH32-W2	2"	50
782051 28082	BCH12-W6	$\frac{3}{4}$ "	50
781011 95567	BCH21-W6	$1\frac{5}{16}$ "	50
781011 95569	BCH32-W6	2"	50


(See pages 260-261 for technical data.)

Read safety/installation instruction sheets in packages before use.



Communication & Low Voltage

- Supports cable above ceiling grid and allows 360° rotation.
- Provides compliance with the EIA/TIA requirements.
- Permits dropwire attachment if required.
- Qwik-Latch cable retainer included with each hook.
- Static Load Capacity: 30 Lbs.
- Finish: Pre-galvanized



Communication & Low Voltage

Cable To T-Bar Fasteners



UPC/Part Number	Catalog Number	Description	Box Qty.
782051 28083	BCH12-A28	3/4"	50
781011 04857	BCH21-A28	15/16"	50
781011 04858	BCH32-A28	2"	50

(See pages 260-261 for technical data.)

Read safety/installation instruction sheets in packages before use.